

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 18/03/2024 Version: 10.46

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: SHADES - MARINE BREEZE (MD) Trade name

UFI : 8XC3-80RC-W00K-1SS8

Product code : 46321 Type of product : Aerosol Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

Use of the substance/mixture : Air Freshener

1.2.2. Uses advised against

No additional information available

V¦*•oÁP^*a?}^AÛ/^¦çã&^•ÁŠcå Ú¦āj&āj|^ÁP[*•^Á 1.3. Details of the supplier of

Leamore Lane Ó|[¢, 2&@Á Yade ad Y ÙGÁ ÚÙ

Ò{æ∰kÁÁnæp^∙Od*•c@ygiene.co.uk

0370 3500 966

1.4. Emergency telephone number

0370 3500 966 Mon-Fri 09:00-17:00

NHS 111 (Out of hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Serious eye damage/eye irritation, Category 2 H319 Hazardous to the aquatic environment - Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Document generated @ 27/04/2024 18:12:35 Page 1 of 11

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229

Serious eye damage/eye irritation, Category 2 H319

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

311302

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P264 - Wash hands thoroughly after handling. P273 - Avoid release to the environment.

P280 - Wear eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

EUH-statements : EUH208 - Contains Benzyl salicylate, (R)-p-mentha-1,8-diene; d-limonene. May produce an

allergic reaction.

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Document generated @ 27/04/2024 18:12:35 Page 2 of 11

Safety Data Sheet

butane substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	30 – 60	Flam. Gas 1A, H220 Press. Gas
propane substance with national workplace exposure limit(s) (IE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	15 – 30	Flam. Gas 1A, H220

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane substance with national workplace exposure limit(s) (IE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	15 – 30	Flam. Gas 1A, H220 Press. Gas
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	10 – 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9	0.1 – 1	Skin Sens. 1, H317
(R)-p-mentha-1,8-diene; d-limonene	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00-7 REACH-no: 01-2119529223-47	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Document generated @ 27/04/2024 18:12:35

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects

: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation

High concentration of vapours may induce: headache, nausea, dizziness.

Symptoms/effects after skin contact

: Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact

: Causes eye irritation.

Symptoms/effects after ingestion

: May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

Treat symptomatically.

Suitable extinguishing media

: Carbon dioxide. Dry powder. Foam.

Fire hazard Explosion hazard

Extremely flammable aerosol. Explosion risk in case of fire.

Firefighting instructions

: Use water spray or fog for cooling exposed containers.

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source. Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures

exceeding 50°C/122°F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.
Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

Document generated @ 27/04/2024 18:12:35 Page 4 of 11

No additional information available

8.1.1 National occupational exposure and biological limit values

propane (74-98-6)		
Ireland - Occupational Exposure Limits		
Local name	Propane	
OEL TWA [2]	1000 ppm	
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)	
Regulatory reference	Chemical Agents Code of Practice 2020	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Document generated @ 27/04/2024 18:12:35 Page 5 of 1

isobutane (75-28-5)			
Ireland - Occupational Exposure Limits			
Local name	Butane, all isomers: Isobutane		
OEL STEL	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
propan-2-ol; isopropyl alcohol; isopropanol (6	67-63-0)		
Ireland - Occupational Exposure Limits	•		
Local name	Isopropyl alcohol		
OEL TWA [2]	200 ppm		
OEL STEL	400 ppm		
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018		
United Kingdom - Occupational Exposure Limits			
Local name	Propan-2-ol		
WEL TWA (OEL TWA) [1]	999 mg/m³		
WEL TWA (OEL TWA) [2]	400 ppm		
WEL STEL (OEL STEL)	1250 mg/m³		
WEL STEL (OEL STEL) [ppm]	500 ppm		
Regulatory reference	EH40/2005 (Third edition, 2018). HSE		
butane (106-97-8)			
Ireland - Occupational Exposure Limits			
Local name	Butane		
OEL TWA [2]	1000 ppm		
OEL STEL	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Butane		
WEL TWA (OEL TWA) [1]	1450 mg/m³		
WEL TWA (OEL TWA) [2]	600 ppm		
WEL STEL (OEL STEL)	1810 mg/m³		
WEL STEL (OEL STEL) [ppm]	750 ppm		
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Document generated @ 27/04/2024 18:12:35 Page 6 of 11

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Not required for normal conditions of use

Hand protection:

In case of repeated or prolonged contact wear gloves

Other skin protection

Materials for protective clothing:

Not required for normal conditions of use

8.2.2.3. Respiratory protection

Respiratory protection:

Not required for normal conditions of use

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

: Liquid Physical state : Colourless. Colour : Aerosol. Appearance Odour : Fresh. Odour threshold : Not available : Not available Melting point : Not available Freezing point **Boiling** point : Not available Flammability : Not available Explosive limits : Not available Lower explosive limit (LEL) : Not available Upper explosive limit (UEL) : Not available : Not applicable Flash point Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available pН : Not available Viscosity, kinematic Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Document generated @ 27/04/2024 18:12:35 Page 7 of 1'

Vapour pressure at 50°C : Not available Density : Not available

Relative density : 0.6

Relative vapour density at 20°C : Not available : Not applicable Particle size : Not applicable Particle size distribution Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 91.45011738

9.2.2. Other safety characteristics

No additional information available

Pressurised container: May burst if heated.

Stable under normal conditions.

No additional information available

Direct sunlight. Heat. Open flame.

No additional information available

10.6. Hazardous decomposition products

No additional information available

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Document generated @ 27/04/2024 18:12:35 Page 8 of 1'

propan-2-ol; isopropyl alcohol; isopropanol STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure : Not classified Aspiration hazard : Not classified Vaporizer Aerosol

No additional information available

Hazardous to the aquatic environment, short–term :

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

: Harmful to aquatic life with long lasting effects.

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	9640 mg/l
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l

No additional information available

Partition coefficient n-octanol/water (Log Pow)	0.05

No additional information available

No additional information available

12.6. Endocrine disrupting properties

No additional information available

No additional information available

Product/Packaging disposal recommendations : Do not pierce or burn, even after use.

In accordance with ADR / IMDG / IATA Safety Data Sheet

Document generated @ 27/04/2024 18:12:35

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.1. UN number or ID number

UN-No. (ADR) : UN 1950 UN-No. (IMDG) : UN 1950 UN-No. (IATA) : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS Proper Shipping Name (IMDG) **AEROSOLS** Proper Shipping Name (IATA) : Aerosols, flammable

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D) Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1 2.1

: Danger labels (ADR)



IMDG

Transport hazard class(es) (IMDG) : 2.1 Danger labels (IMDG) 2.1

IATA

Transport hazard class(es) (IATA) : 2.1 Danger labels (IATA) : 2.1

14.4. Packing group

: Not applicable Packing group (ADR) Packing group (IMDG) : Not applicable Packing group (IATA) : Not applicable

14.5. Environmental hazards

: No Dangerous for the environment Marine pollutant

Other information : No supplementary information available

14.6. Special precautions for user

Document generated @ 27/04/2024 18:12:35 Page 10 of 11

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, I

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

IBC code : Not applicable.

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

15.1.2. National regulations

No additional information available

No additional information available

Document generated @ 27/04/2024 18:12:35 Page 11 of 11

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
EUH208	UH208 Contains Benzyl salicylate, (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:		
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Press. Gas	Gases under pressure	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Eye Irrit. 2	H319	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.