



# Trust Hygiene Services Ltd

## Safety Data Sheet

---

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : TFX PURELL® Advanced Hand Rub

Product code : 11324

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Disinfectant product

#### 1.3. Details of the supplier of the safety data sheet

Trust Hygiene Services Ltd, Principle House, Leamore Lane, Bloxwich, Walsall, WS2 7PS

Email: [sales@trusthygiene.co.uk](mailto:sales@trusthygiene.co.uk) | Telephone: 0370 3500 988 (09:00 to 17:00 Mon-Fri)

#### 1.4. Emergency telephone number :

(UK) NHS 111 / 999

---

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

Biocidal mixture (see section 15).

### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

GHS02

Signal Word :

WARNING

Hazard statements :

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautionary statements - Response :

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64-17-5 EC: 200-578-6  ETHANOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	50 $\leq$ x % < 100
INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7  PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	2.5 $\leq$ x % < 10
CAS: 56-81-5 EC: 200-289-5  GLYCERINE		[1]	0 $\leq$ x % < 1
INDEX: 603-070-00-6 CAS: 124-68-5 EC: 204-709-8  2-AMINO-2-METHYLPROPANOL	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315 Aquatic Chronic 3, H412	[1]	0 $\leq$ x % < 1
INDEX: 601-017-00-1 CAS: 110-82-7 EC: 203-806-2  CYCLOHEXANE	GHS02, GHS08, GHS07, GHS09 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[1]	0 $\leq$ x % < 1

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

---

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of swallowing :

Seek medical attention, showing the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

---

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- carbon dioxide (CO<sub>2</sub>)
- powder
- foam
- dry sand

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

---

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Remove and wash contaminated clothing before re-using.

#### Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

#### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

---

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m <sup>3</sup>	VME-ppm	VLE-mg/m <sup>3</sup>	VLE-ppm	Notes
110-82-7	700	200	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
67-63-0	200 ppm	400 ppm	-	-	-
56-81-5	10 mg/m <sup>3</sup>	-	-	-	-
110-82-7	100 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
64-17-5	500 ml/m <sup>3</sup>	960 mg/m <sup>3</sup>	2(II)	DFG, Y
67-63-0	200 ml/m <sup>3</sup>	500 mg/m <sup>3</sup>	2(II)	DFG, Y
124-68-5	1 ml/m <sup>3</sup>	4,6 mg/m <sup>3</sup>	2 (I)	AGS
110-82-7	200 ml/m <sup>3</sup>	700 mg/m <sup>3</sup>	4(II)	DFG

- Belgium (Order of 19/05/2009, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
67-63-0	400 ppm	500 ppm	-	-	-

56-81-5	10 mg/m <sup>3</sup>	-	-	-	-	-
110-82-7	300 ppm	-	-	-	-	-
- Denmark (2007) :						
CAS	TWA :	TWA :	Anm :			
64-17-5	1000 ppm	1900 mg/m <sup>3</sup>	-			
67-63-0	200 ppm	490 mg/m <sup>3</sup>	-			
110-82-7	50 ppm	172 mg/m <sup>3</sup>	-			
- France (INRS - ED984 :2008) :						
CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84
67-63-0	-	-	400	980	-	84
56-81-5	-	10	-	-	-	-
110-82-7	200	700	-	-	-	84
- Finland (HTP-värden 2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 ppm	1300 ppm	-	-	-	
67-63-0	200 ppm	250 ppm	-	-	-	
110-82-7	100 ppm	250 ppm	-	-	-	
- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), Mayo 2010) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 ppm	-	-	-	-	
67-63-0	400 ppm	500 ppm	-	-	-	
56-81-5	10 mg/m <sup>3</sup>	-	-	-	-	
110-82-7	300 ppm	600 ppm	-	-	-	
- Ireland (Code of practice for the safety, Health and Welfare at Work, 2010) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 ppm	-	-	-	-	
67-63-0	400 ppm	500 ppm	-	-	-	
56-81-5	10 mg/m <sup>3</sup>	-	-	-	-	
110-82-7	100 ppm	300 ppm	-	-	-	
- Norway (Veiledning om administrative normer for forurensning i arbeidsatmosfære, May 2007) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	500 ppm	-	-	-	-	
67-63-0	100 ppm	-	-	-	-	
110-82-7	150 ppm	-	-	-	-	
- Netherlands / MAC-waarde (SER, 4 May 2010) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	500 ppm	-	-	-	-	
67-63-0	250 ppm	-	-	-	-	
56-81-5	10 mg/m <sup>3</sup>	-	-	-	-	
110-82-7	250 ppm	500 ppm	-	-	-	
- Poland (2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1900 mg/m <sup>3</sup>	-	-	-	-	
67-63-0	900 mg/m <sup>3</sup>	1200 mg/m <sup>3</sup>	-	-	-	
56-81-5	10 mg/m <sup>3</sup>	-	-	-	-	
110-82-7	300 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>	-	-	-	
Czech Republic (Regulation No. 361/2007) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>	-	-	-	
67-63-0	500 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>	-	-	-	
110-82-7	500 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>	-	-	-	
Slovakia (Regulation No. 300/2007) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	500 ppm	960 mg/m <sup>3</sup>	II.1			
67-63-0	200 ppm	500 mg/m <sup>3</sup>	II.1			
110-82-7	200 ppm	700 mg/m <sup>3</sup>	II.1			

- Switzerland (SUVA 2009) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Temps :	RSB :
64-17-5	960	500	1920	1000	4x15	-
67-63-0	500	200	1000	400	4x15	B
56-81-5	50 i	-	100 i	-	4x15	-
110-82-7	700	200	2800	800	4x15	B

- Sweden (AFS 2007:2) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	500 ppm	1000 ppm	-	-	-
67-63-0	150 ppm	250 ppm	-	-	-
110-82-7	300 ppm	370 ppm	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
67-63-0	400 ppm	500 ppm	-	-	-
56-81-5	10 mg/m3	-	-	-	-
110-82-7	100 ppm	300 ppm	-	-	-

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

---

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state :	Fluid liquid.
Color:	colourless
Odour:	alcoholic

#### Important health, safety and environmental information

pH :	7.50 +/- 1. Neutral.
Flash Point :	24.00 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	0,88 g/cm <sup>3</sup>
Water solubility :	Soluble.
Viscosity :	6.000 - 17.000 mm <sup>2</sup> /s (20 °C)
% VOC :	< 75%

### 9.2. Other information

No data available.

---

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces
- frost

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

#### 11.1.1. Substances

No toxicological data available for the substances.

#### 11.1.2. Mixture

No toxicological data available for the mixture.

---

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

---

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.  
Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

**14.1. UN number**

1987

**14.2. UN proper shipping name**

UN1987=ALCOHOLS, N.O.S.  
(ethanol, propan-2-ol)

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	274 601	E1	3	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	III	5 L	F-E,S-D	223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A180	E1
	3	-	III	Y344	10 L	-	-	A3 A180	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC)**

:

Name	CAS	%	Product-type
ETHANOL	64-17-5	631.67 g/kg	01



Product-type 1 : Human hygiene.

## 15.2. Chemical safety assessment

No data available.

---

### SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.